



## **BA 123 ROOF RACK FITTING INSTRUCTIONS**

### **KIT CONTENTS**

**3X LONG LEGS (LH)  
3X LONG LEGS (RH)  
1X SHORT LEG (LH FRONT)  
1X SHORT LEG (RH FRONT)  
8X GUTTER CLAMPS  
2X LADDER BRACKETS  
16X M8 X 30 BOLTS  
16X M8 X 25 BOLTS  
16X M8 NYLOC NUTS  
16X M8 SPRING WASHERS  
6X M10 X 25 BOLTS  
6X M10 NYLOC NUTS  
1X M12 NUT & WASHER  
1X HANDWHEEL**



**FIT LEGS TO ROOF RACK USING M8X 30 BOLTS & NUTS ENSURING THE SHORT LEGS ARE FITTED TO THE FRONT SECTION OF ROOF RACK, DO NOT FULLY TIGHTEN FIXINGS AT THIS STAGE ANY FREEPLAY WILL BE REQUIRED TO LEVEL ROOF RACK AT LATER STAGE,**

**FIT LADDER BRACKETS TO ROOF RACK USING M10 X 25 BOLTS & NUTS AND ATTACH LADDER TO BRACKET USING M12 NUT & WASHER.**

**FIT REAR SECTION TO ROOF AND FULLY EXTEND LADDER, THE RACK IS CORRECTLY POSITIONED WHEN BOTTOM LEG ON LADDER IS RESTING AGAINST REAR CROSSMEMBER.**

**FIT FRONT SECTION AND LEVEL ROOF RACK UTILISING THE FREE PLAY IN LEG FIXINGS AND TIGHTEN, FIT THE GUTTER CLAMPS USING M8X 25 BOLTS & SPRING WASHERS.**

**PLEASE ENSURE THE SHORT BOLTS ARE USED TO SECURE THE GUTTER CLAMPS TO LEGS AND EXCESSIVE FORCE IS AVOIDED WHEN TIGHTENING THESE FIXINGS.**